YoLink Fob

Overview

This driver represents a single YoLink fob or remote in Control4 and requires the **YoLink** gateway. Bind this driver's **YoLink Gateway** connection to the matching `YOLINK_FOB` provider on the gateway. **Auto Setup** can add and bind instances automatically.

Physical button presses fire Composer programming events. Two-button fobs use buttons 1 and 2; four-button remotes use all four. Extra events on a two-button fob never fire.

See the **YoLink** documentation for account setup and gateway configuration.

Properties

Property	Description
Cloud Status	DriverCentral license status (read-only)
Automatic Updates	Allow automatic driver updates when available
Driver Version	Packaged driver version (read-only)
Log Level	Logging verbosity; resets to Off after about 1 hour when not Off
Auto Rename Driver	When On (default), renames the driver in Composer to the YoLink device name
YoLink Device ID	YoLink device identifier, set by gateway (read-only)
Device Name	Device name from YoLink, set by gateway (read-only)
Device Type	YoLink device type, set by gateway (read-only)
Model Name	Device model name, set by gateway (read-only)
Battery	Battery level reported by YoLink (0–4; 4 = full) (read-only)

Bindings

Connection	Class	Notes
YoLink Gateway	`YOLINK_FOB`	Bind to the matching provider on the YoLink gateway

Programming

Events

Event	Description
Button 1 Pressed	Short press on button 1
Button 1 Long Pressed	Long press on button 1
Button 2 Pressed	Short press on button 2
Button 2 Long Pressed	Long press on button 2
Button 3 Pressed	Short press on button 3
Button 3 Long Pressed	Long press on button 3
Button 4 Pressed	Short press on button 4
Button 4 Long Pressed	Long press on button 4

Variables

Variable	Type	Notes
BATTERY	NUMBER	YoLink battery level (0–4; 4 = full)

Use **Reset Driver** when rebinding a different device to clear leftover variables.

Actions

Action	Description
Refresh Status	Requests the current device state from the gateway
Reset Driver	Clears programming variables. Use when rebinding a different device; confirm with Yes

Support

If you have questions or issues with this driver, contact us at support@solidified.co or call/text +1 (561) 444-9960. You can also submit a support ticket at DriverCentral.

Changelog

v20261104 - 2026-11-04

Changed

- Changed programming variables so they are no longer removed when a device report does not include that capability; use Reset Driver to clear them.

v20261102 - 2026-11-02

Added

- Added Reset Driver action to clear connections and programming variables when rebinding a different device.

Fixed

- Fixed a situation where programming variables could be cleared after a controller reboot.

v20260826 - 2026-08-26

Added

- Added support for water valves and FlowSmart devices.
- Added support for remotes and fobs (including short and long press programming events).

- Added programming variables on the sensor subdriver.
- Added battery property and programming variable for battery-powered devices.

v20260617 - 2026-06-17

Added

- Added support for smoke/CO alarm sensors.

v20260611 - 2026-06-11

Added

- Initial release.